

Supplier TOSHIBA CARRIER CORPORATION

Indoor unit RAS-24J2KVG-E

Outdoor unit RAS-24J2AVG-E

Sound power level

indoor unit (cooling) dB 63

outdoor unit (cooling) dB 70

indoor unit (heating) dB 58

outdoor unit (heating) dB 70

Refrigerant

Type R32

Global Warming Potential kgCO₂eq 675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class A++

Design load (P_{designc}) kW 6.5

Seasonal efficiency (SEER) 6.10

Seasonal electricity consumption (Q_{CE}) kWh/annum 373

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+	A++	x
Design load (Pdesignh)	kW	5.4	2.9	x,x
Seasonal efficiency (SCOP)		4.00	4.90	x,xx
Seasonal electricity consumption (Q _{HE})	kWh/annum	1890	824	x
Back up heating capacity		kW	1.02	
Declared capacity for heating, at indoor temperature 20°C and outdoor temperature T_j.				
T _j = -7°C (Pdh)	kW	4.78	-	x,xx
T _j = 2°C (Pdh)	kW	2.91	2.91	x,xx
T _j = 7°C (Pdh)	kW	1.87	1.87	x,xx
T _j = 12°C (Pdh)	kW	0.90	0.90	x,xx
T _j =bivalent temperature (Pdh)	kW	4.78	2.91	x,xx
T _j =operation limit (Pdh)	kW	3.71	3.71	x,xx
T _j = -15°C (Pdh)	kW	-	-	x,xx